



## 1SS400

Preliminary

DIODE

### SWITCHING DIODE


#### DESCRIPTION

The UTC **1SS400** is a switching diode, it uses UTC's advanced technology to provide customers with high speed switching and low reverse leakage, etc.

#### FEATURES

- \* High speed switching
- \* Low reverse leakage

#### SYMBOL





#### ORDERING INFORMATION

Ordering Number		Package	Pin Assignment		Packing
Lead Free	Halogen Free		1	2	
1SS400L-CC2-R	1SS400G-CC2-R	SOD-523	A	K	Tape Reel

Note: Pin Assignment: A: Anode, K: Cathode

<p>1SS400L-CC2-R</p> <ul style="list-style-type: none"> <li>(1) Packing Type</li> <li>(2) Package Type</li> <li>(3) Halogen Free</li> </ul>	<ul style="list-style-type: none"> <li>(1) R: Tape Reel</li> <li>(2) CC2 : SOD-523</li> <li>(3) L: Lead Free, G: Halogen Free</li> </ul>
---	--

#### MARKING



■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT
DC Blocking Voltage	$V_R$	80	V
Peak Repetitive Reverse Voltage	$V_{RRM}$	90	V
Average Rectified Output Current	$I_O$	100	mA
Power Dissipation	$P_D$	150	mW
Operating Junction Temperature	$T_J$	-55~+125	°C
Storage Temperature	$T_{STG}$	125	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Forward Voltage	$V_F$	$I_F=100\text{mA}$			1.2	V
Reverse Leakage Current	$I_R$	$V_R=80\text{V}$			0.1	$\mu\text{A}$
Reverse Recovery Time	$T_{RR}$	$V_R=6\text{V}, I_F=10\text{mA}, R_L=100\Omega$			4	ns

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.