

SMD LINE FILTER

SF0903, 0904 SERIES

FEATURES:

- Low profile very effective in space conscious applications
- Low resistance filters have been designed for excellent electrical isolation
- High quality toroidal core
- Wide frequency range over 1000MHz
- Lead free construction

OPTIONS:

- Tape & Reel is Standard (Qty:1500pcs)
- Bulk packaging Available for Smaller Quantities

COMMON APPLICATIONS:


- Provide common mode noise attenuation
- Reduce conducted noise
- For the suppression of EMI in data lines and signal lines, e.g., CAN Bus

ELECTRICAL CHARACTERISTICS:

Part Number	L(μH) 100K/0.1V	L-L(μH) 100K/0.02V	C(pF) 100K/0.02V	DCR(Ω) max.	Tums Ratio	Insertion Loss		Impedance(z)	
						Freq.rang	db	Freq.rang	min(Ω)
SF0903									
470YAB	47.0 min.	0.18 ⁺⁰	20 ⁺⁰	0.4	1:1	1~100MHz	20 ⁰	10~30MHz	1000
200YAB	20.0 min.	0.10 ⁺⁰	18 ⁺⁰	0.4	1:1:1	30~300MHz	20 ⁰	30~100MHz	800


Part Number	L(1-4) @100KHz,0.1Vrms (μH)	L-L(1-4) @100KHz,0.1Vrms typ.(2-3 short) max.	DCR (winding) (Ω) max.	Rated Current max.	winding
SF0904					
110YL	11 ± 25%	0.050(μH)	0.120	0.50 A	Bifilar
250YL	25 ± 25%	1.500(μH)	0.200	0.50 A	Bifilar
510YL	51 ± 25%	2.000(μH)	0.300	0.50 A	Bifilar
471YL	470 ± 25%	0.280(μH)	0.280	0.50 A	Bifilar
102YL	1000 ± 25%	0.290(μH)	0.400	0.50 A	Bifilar
472YL	4700 ± 25%	0.300(μH)	0.700	0.20 A	Bifilar

TECHNICAL INFORMATION & PHYSICAL CHARACTERISTICS:



- Materials:
1. Core: Ferrite Toroidal Core(0903-A), Ferrite Core(0904)
 2. Wire: Enamelled Copper Wire(Class F)
 3. Base: Phenolic(0903-A), PPHS(UL940V-0)(0904)
 4. Terminal: Cu / Ni / Sn (0904)
 5. Adhesive: Epoxy Resin (0904)
 6. Case: PPHS(UL940V-0)(0904)

- General Specification:
1. Storage Temperature:
 - 40°C -- +105°C(0903-A)
 - 40°C -- + 135°C(0904)
 2. Operation Temperature:
 - 25°C -- + 85°C(0903-A)
 - 40°C -- + 135°C(0904)
 3. Temperature Rise Included:
 - 30°C max at Rated Current (0904)
 4. Resistance to solder heat:
 - 260°C, 10 secs.




SF 0903-A SERIES

SF 0904 SERIES

Dimensions(mm)

Series	A	A1	B	B1	C	D
SF0903	9.20max.	7.24 typ.	6.60 max	5.08 typ.	2.50 max	2.54 typ.

Series	A1	A	B	C	D	E	F	H	I	J	K	L	M
SF0904L	9.20 ± 0.3	7.1 typ.	6.00 ± 0.3	5.00 ± 0.3	5.32 typ.	2.49 typ.	0.60 typ.	1.92 typ.	0.25 typ.	9.60 ref.	3.40 ref.	2.20 ref.	1.00 ref.



“•”: Polarity
 Note:
 All specifications subject to change without notice.