

Sealed SMT Tact switches

INT-1133S Series 12×12mm, Sealed with Rubber, Hard actuator, Surface mount type



- ▶ **Features :** IP67
- ▶ **Applications :** Home appliances, Office devices, Industrial equipments
- ▶ **Specifications :**

Rating	DC 12V 50mA
Contact resistance	100mΩ Max.
Travel (mm)	0.3±0.1

▶ Part list

Part No.	Length (mm)	Operating force	Life	QTY per pack (Tape & reel)
INT-1133S43A	4.3	230±50gf	100,000 Cycles Min.	850
INT-1133S75A	7.5			500
INT-1133S85A	8.5			400
INT-1133S95A	9.5			500
INT-1133ST73A	7.3			500 (Plastic bag)
INT-1133SF12A	12.0			

▶ Drawing

Length (mm)	Dimensions (mm)	Circuit diagram	PCB Dimension
4.3, 7.5, 8.5, 9.5mm		<p>Circuit diagram</p>	<p>PCB Dimension</p>
7.3mm		<p>Circuit diagram</p>	<p>PCB Dimension</p>
12mm		<p>Circuit diagram</p>	<p>PCB Dimension</p>

TACT Switches
 PUSH Switches
 HOOK Switches
 DETECTOR Switches
 SLIDE Switches
 ROTARY Potentiometers
 LEVER Switches
 ROTARY Switches
 CAPS