

OLED DISPLAY SPECIFICATION



RAYSTAR

RAYSTAR Optronics, Inc.
曜凌光電股份有限公司



曜凌光電股份有限公司 Raystar Optronics, Inc.

T: +886-4-2565-0761 | F: +886-4-2565-0760
sales@raystar-optronics.com | www.raystar-optronics.com

REX012864AK SPECIFICATION

General Specification

The Features is described as follow:

- Dot Matrix: 128 x 64
- Module dimension: 73.0 x 41.86 x 2.01 mm
- Active Area: 61.41 x 30.69 mm
- Pixel Size: 0.45 x 0.45 mm
- Pixel Pitch: 0.48 x 0.48 mm
- Display Mode: Passive Matrix
- Display Color: Monochrome
- Drive Duty: 1/64 Duty
- IC: CH1116
- Interface: 6800,8080,4-Wire SPI,I2C
- Size: 2.7 inch

Interface Pin Function

No.	Symbol	Function
1	NC(VSS)	No connection
2	VPP	OLED panel power supply. Generated by internal charge pump. Connect to capacitor. It could be supplied externally.
3	VCOMH	This is a pad for the voltage output high level for common signals. A capacitor should be connected between this pad and VSS.
4	IREF	This is a segment current reference pad. A resistor should be connected between this pad and VSS. Set the current at 18.75uA.
5~12	D7~D0	This is an 8-bit bi-directional data bus that connects to an 8-bit or 16-bit standard MPU data bus. When the serial interface is selected, then D0 serves as the serial clock input pad (SCL) and D1 serves as the serial data input pad (SI). At this time, D2 to D7 are set to high impedance. When the I2C interface is selected, then D0 serves as the serial clock input pad (SCL) and D1 serves as the serial data input pad (SDAI). At this time, D2 to D7 are set to high impedance.
13	E/ $\overline{\text{RD}}$	This is a MPU interface input pad. When connected to an 8080 series MPU, it is active LOW. This pad is connected to the $\overline{\text{RD}}$ signal of the 8080 series MPU, and the data bus is in an output status when this signal is "L". When connected to a 6800 series MPU, this is active HIGH. This is used as an enable clock input of the 6800 series MPU. When $\overline{\text{RD}}$ = "H": Enable. When $\overline{\text{RD}}$ = "L": Disable.
14	$\overline{\text{WR}}$ (R/ $\overline{\text{W}}$)	This is a MPU interface input pad. When connected to an 8080 MPU, this is active LOW. This pad connects to the 8080 MPU $\overline{\text{WR}}$ signal. The signals on the data bus are latched at the rising edge of the $\overline{\text{WR}}$ signal. When connected to a 6800 Series MPU: This is the read/write control signal input terminal. When R/ $\overline{\text{W}}$ = "H": Read. When R/ $\overline{\text{W}}$ = "L": Write.
15	A0	This is the Data/Command control pad that determines whether the data bits are data or a command. A0 = "H": the inputs at D0 to D7 are treated as display data. A0 = "L": the inputs at D0 to D7 are transferred to the command registers. In I2C interface, this pad serves as SA0 to distinguish the different address of OLED driver.

16	$\overline{\text{RES}}$	This is a reset signal input pad. When $\overline{\text{RES}}$ is set to “L”, the settings are initialized. The reset operation is performed by the $\overline{\text{RES}}$ signal level.			
17	$\overline{\text{CS}}$	This pad is the chip select input. When $\overline{\text{CS}}$ = “L”, then the chip select becomes active, and data/command I/O is enabled.			
18	NC	No connection			
19	IM2	These are the MPU interface mode select pads.			
		8080	I2C	6800	4-wire SPI
	IM1	1	1	0	0
	IM2	1	0	1	0
20	IM1	Note (1) 0 is connected to VSS (2) 1 is connected to VDD1			
21	VDD1	Power supply input			
22~28	NC	No connection			
29	VSS	Ground.			
30	NC(VSS)	No connection			

Technical drawing of the LCD module assembly, showing dimensions and labels for various components.

Top View Dimensions:

- Overall width: 73 ± 0.2
- Width to Pull Tape: $72(\text{Pol.})$
- Width to VA: $63.41(\text{VA})$
- Width to AA: $61.41(\text{AA})$
- Offset from top edge: 0.5
- Offset from top edge: 4.795
- Offset from top edge: 5.795

Active Area: 2.7" 128x64 Pixels

Side View Dimensions:

- Overall height: 105.57 ± 1
- Distance from top edge to Shading Tape: 28.75 ± 0.5
- Shading Tape width: (10)
- Distance from bottom edge to Stiffener: (8)
- Stiffener width: 7
- Stiffener height: 30
- Stiffener hole diameter: $2 \times \phi 0.8$
- Stiffener hole offset: 1
- Stiffener hole offset: 13.5
- Stiffener hole offset: 1

Detail View Dimensions:

- Overall width: 2.01 ± 0.2
- Offset from top edge: 0.7
- Offset from top edge: 1.1
- Glue thickness: 2.0 Max. (Non-Bending area)
- Stiffener width: 4.5
- Contact Side offset: 0.3 ± 0.03

Labels:

- Pull Tape
- Polarizer
- Glue
- Shading Tape
- Stiffener
- Contact Side

Other Labels:

- 128*64
- C64(COM63)
- C2(COM1)
- S128(SEG127)
- Seg&Com
- FPC Cont
- Scale

The non-specified tolerance of dimension is ± 0.3 mm .

Absolute Maximum Ratings

Parameter	Symbol	Min	Max	Unit
Supply Voltage for Logic	VDD1	-0.3	3.6	V
Supply Voltage for Display	VPP	0	14.5	V
Operating Temperature	TOP	-40	+80	°C
Storage Temperature	TSTG	-40	+85	°C

Electrical Characteristics

DC Electrical Characteristics

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage for Logic	VDD1	—	1.65	3.0	3.3	V
Supply Voltage for Display	VPP	—	6.4	13.0	13.5	V
High Level Input	VIH	—	0.8×VDD1	—	VDD1	V
Low Level Input	VIL	—	VSS	—	0.2×VDD1	V
High Level Output	VOH	—	0.8×VDD1	—	VDD1	V
Low Level Output	VOL	—	VSS	—	0.2×VDD1	V
Display 50% Pixel on	IPP	VPP =13V	—	15	30	mA