



# RGBP161506-PATC2

## Multi-Wavelength SMD Type

### Features

- Top view 1615 package
- Wide viewing angle
- RGB individual control
- High reliability
- RoHS compliance


### Applications

- General lighting
- Indoor signage display applications
- Switch light
- Decorative and Entertainment lighting


### Description

The RGBP161506-PATC2 is a high brightness device designed for demanding applications in efficiency and reduced space. An ideal device in emphasizing visual effects, advertisement, decoration as well as general backlighting needs.

### Package Outline



### Schematic





# RGBP161506-PATC2

## Multi-Wavelength SMD Type

### Absolute Maximum Rating at 25°C

Symbol	Parameters		Ratings	Units	Notes
I <sub>F</sub>	Continuous Forward Current	R	25	mA	
		G	25		
		B	25		
I <sub>FP</sub>	Peak Forward Current	R	60	mA	1
		G	60		
		B	60		
V <sub>R</sub>	Reverse Voltage		5	V	
T <sub>opr</sub>	Operating Temperature		-40 ~ +85	°C	
T <sub>stg</sub>	Storage Temperature		-40 ~ +100	°C	
T <sub>sol</sub>	Soldering Temperature		260	°C	2
P <sub>D</sub>	Power Dissipation at(or below) 25°C Free Air Temperature	R	60	mW	
		G	95		
		B	95		

### Electro-Optical Characteristics *T<sub>A</sub> = 25°C (unless otherwise specified)*

#### Optical Characteristics (Red)

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
I <sub>v</sub>	Luminous Intensity	I <sub>F</sub> =20mA	112	-	285	mcd	3
λ <sub>d</sub>	Dominant Wavelength	I <sub>F</sub> =20mA	617	622	627	nm	
θ <sub>1/2</sub>	Angle of Half Intensity	I <sub>F</sub> =20mA	-	±65	-	deg	

#### Electrical Characteristics (Red)

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
V <sub>F</sub>	Forward Voltage	I <sub>F</sub> =20mA	1.7	-	2.4	V	
I <sub>R</sub>	Reverse Current	V <sub>R</sub> =5V	-	-	1	μA	



## RGBP161506-PATC2

### Multi-Wavelength SMD Type

#### Optical Characteristics (Green)

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
I <sub>v</sub>	Luminous Intensity	I <sub>F</sub> =20mA	450	-	1120	mcd	3
λ <sub>d</sub>	Dominant Wavelength	I <sub>F</sub> =20mA	515	523	530	nm	4
θ <sub>1/2</sub>	Angle of Half Intensity	I <sub>F</sub> =20mA	-	±65	-	deg	

#### Electrical Characteristics (Green)

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
V <sub>F</sub>	Forward Voltage	I <sub>F</sub> =20mA	2.7	-	3.3	V	
I <sub>R</sub>	Reverse Current	V <sub>R</sub> =5V	-	-	1	μA	

#### Optical Characteristics (Blue)

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
I <sub>v</sub>	Luminous Intensity	I <sub>F</sub> =20mA	112	-	285	mcd	3
λ <sub>d</sub>	Dominant Wavelength	I <sub>F</sub> =20mA	460	467	475	nm	4
θ <sub>1/2</sub>	Angle of Half Intensity	I <sub>F</sub> =20mA	-	±65	-	deg	

#### Electrical Characteristics (Blue)

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
V <sub>F</sub>	Forward Voltage	I <sub>F</sub> =20mA	2.7	-	3.3	V	
I <sub>R</sub>	Reverse Current	V <sub>R</sub> =5V	-	-	1	μA	

#### Notes:

1. I<sub>FP</sub> Conditions--Pulse Width ≤ 100μs and Duty ≤ 10%.
2. Soldering time ≤ 10 seconds.



# RGBP161506-PATC2

## Multi-Wavelength SMD Type

### 3. Bin Range of Luminous Intensity

Red				
Bin Code	Min	Max	Unit	Condition
Q	112	180	mcd	I <sub>F</sub> =20mA
R	180	285		
Green				
T	450	715	mcd	I <sub>F</sub> =20mA
U	715	1120		
Blue				
Bin Code	Min	Max	Unit	Condition
Q	112	180	mcd	I <sub>F</sub> =20mA
R	180	285		

Tolerance of Luminous Intensity  $\pm 10\%$

### 4. Bin Range of Dominant Wavelength

Green				
Bin Code	Min	Max	Unit	Condition
A4	515	520	nm	I <sub>F</sub> =20mA
A5	520	525		
A6	525	530		
Blue				
A5	460	465	nm	I <sub>F</sub> =20mA
A6	465	470		
A7	470	475		







Tolerance of Dominant Wavelength:  $\pm 1\text{nm}$ .



# RGBP161506-PATC2


## Multi-Wavelength SMD Type

### Typical Characteristic Curves





### Typical Characteristic Curves



View Angle (°)  
**Figure 7**


www.sig



# RGBP161506-PATC2


## Multi-Wavelength SMD Type

### Package Dimension *All dimensions are in mm, unless otherwise stated*



Note: Tolerance unless mentioned is  $\pm 0.1$ mm

### Recommended Soldering Mask *All dimensions are in mm, unless otherwise stated*



Note: Tolerance unless mentioned is  $\pm 0.1$ mm

### Ordering Information


Part Number	Description	Quantity
RGBP161506-PATC2	Tape & Reel	2000 pcs




# RGBP161506-PATC2

## Multi-Wavelength SMD Type

### Reel Dimension *All dimensions are in mm, unless otherwise stated*



### Tape Dimension *All dimensions are in mm, unless otherwise stated*




Note: Tolerance unless mentioned is  $\pm 0.1$ mm





### Label Form Specification



CPN : Customer Part Number  
Part no: CTM Production Number  
Serial no: Production Number  
Lot no: Lot number  
Q'ty: Packing Quantity  
Date Code: Manufacture Date  
IV : Bin Code of Luminous Intensity  
WD : Bin Code of Dominant Wavelength  
VF : Bin Code of Forward Voltage  
MADE IN CHINA: Production Place

### Storage Condition


1. Do not open moisture proof bag before the products are ready to use.
2. The moisture barrier bag should be stored at 30°C and 90%R.H. max. before opening.  
Shelf life of non-opened bag is 12 months after the bag sealing date.
3. After opening the moisture barrier bag floor life is 1 year at 30°C/60%RH. max. Unused LEDs should be resealed into moisture barrier bag. (Refer to J-STD-020 Standard)
4. If the moisture absorbent material has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the J-STD-033 Standard conditions.



# RGBP161506-PATC2

## Multi-Wavelength SMD Type

### Reflow Profile



Profile Feature	Pb-Free Assembly Profile
Temperature Min. (Tsmmin)	150°C
Temperature Max. (Tsmmax)	200°C
Time (ts) from (Tsmmin to Tsmmax)	60-120 seconds
Ramp-up Rate (tL to tP)	3°C/second max.
Liquidous Temperature (TL)	217°C
Time (tL) Maintained Above (TL)	60 – 150 seconds
Peak Body Package Temperature	260°C +0°C / -5°C
Time (tP) within 5°C of 260°C	30 seconds
Ramp-down Rate (TP to TL)	6°C/second max
Time 25°C to Peak Temperature	8 minutes max.



## RGBP161506-PATC2 Multi-Wavelength SMD Type

---

### DISCLAIMER

CT MICRO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. CT MICRO DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

---

CT MICRO ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT EXPRESS WRITTEN APPROVAL OF CT MICRO INTERNATIONAL CORPORATION.

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instruction for use provided in the labelling, can be reasonably expected to result in significant injury to the user.*
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.*